

**MICHELIN  
AGRIBIB**

**Standard series**

**For tractors from 60 to 170 HP  
and up to 500 HP with dual fitment  
row crop solution  
(Diameters : 42", 46", 50")**



**High level of performance  
throughout it's life**



**MICHELIN**

*A better way forward*

High level of performance throughout it's life

To find all the information:



Traction capacity



Service life



Robustness



**+ 4% traction capacity with a new tyre, + 22% with a tyre 60% worn** <sup>(1)</sup>

Lug angle 45° for better transfer of tractive force to the ground  
Productivity gains

**Proven radial casing endurance and damage-resistant rubber**

**+ 2 years additional use** <sup>(2)</sup>  
**+ 15% deep tread lugs** <sup>(2)</sup>

R1W lug <sup>(3)</sup> for longer service life

**Self-cleaning capacity**

Hinge in the center of the tread

(1) Source: Analytical test performed on the test tracks at the MICHELIN test and research centre (Ladoux). Compared to competitors. Test conditions: clay/chalky soil - Tyre size: 18.4 R38.

(2) Source: MICHELIN test and research center (Ladoux)  
Calculation: average calculated on 13 popular sizes on the standard market.

(3) Lug depth as defined by the TRA standard.

Sizes														
9.5	R24 TL 112A8/109B	NEW	13.6	R28 TL 123A8/120B		18.4	R34 TL 149A8/146B	NEW	16.9	R38 TL voir 420/85 R38 TL		480/80	R42 TL 156A8/156B	
11.2	R24 TL 119A8/116B	NEW	14.9	R28 TL 134A8/131B	NEW	320/85	R34 TL 133A8/130B		18.4	R38 TL 151A8/148B	NEW	520/85	R42 TL 157A8/157B	
12.4	R24 TL 119A8/116B		16.9	R28 TL 141A8/138B	NEW	380/85	R34 TL 137A8/137B		20.8	R38 TL 159A8/156B	NEW	420/80	R46 TL 151A8/148B	
13.6	R24 TL 124A8/121B	NEW	16.9	R30 TL 137A8/134B		420/85	R34 TL 147A8/147B	NEW	380/80	R38 TL 142A8/139D		480/80	R46 TL 158A8/158B	
14.9	R24 TL 130A8/127B	NEW	18.4	R30 TL 142A8/139B		12.4	R36 TL 124A8/121B		380/95	R38 TL 147A8/147B		520/85	R46 TL 158A8/155B	
16.9	R24 TL 134A8/131B		380/85	R30 TL 135A8/135B		12.4	R38 TL 131A8/128B	NEW	420/85	R38 TL 144A8/144B		480/80	R50 TL 159A8/159B	
12.4	R28 TL 126A8/123B	NEW	420/90	R30 TL 147A8/147B		13.6	R38 TL 128A8/125B		520/85	R38 TL 155A8/155B		480/95	R50 TL 164A8/164B	

## MICHELIN ADVICE

### MACHINE N° 1:

FRONT: .....

PRESSURE: .....(bars / psi)

REAR: .....

PRESSURE: .....(bars / psi)

### MACHINE N° 2:

FRONT: .....

PRESSURE: .....(bars / psi)

REAR: .....

PRESSURE: .....(bars / psi)



agro.michelin.com



www.youtube.com/user/AgMichelin



**MICHELIN**

A better way forward